### **Technical Data Sheet**

# Alathon M6060

High Density Polyethylene



## **Product Description**

*Alathon* M6060 is a medium molecular weight high density homopolymer with extremely low gel content. This resin provides high stiffness and narrow molecular weight distribution for use in cast film applications. Typical applications for this resin are dry food packaging, overwrap and WVTR.

## **Regulatory Status**

For regulatory compliance information, see *Alathon* M6060 <u>Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).</u>

Status Commercial: Active
Availability North America

**Application** Bags & Pouches; Barrier Film; Food Packaging Film; Lamination Film

Market Flexible Packaging

Processing Method Cast Film

Attribute General Purpose; Good Abrasion Resistance; Good Organoleptic Properties; High

Density; Low Gel

|                                  | Nominal | English  | Nominal | SI       |             |
|----------------------------------|---------|----------|---------|----------|-------------|
| Typical Properties               | Value   | Units    | Value   | Units    | Test Method |
| Physical                         |         |          |         |          |             |
| Melt Flow Rate, (190 °C/2.16 kg) | 6.0     | g/10 min | 6.0     | g/10 min | ASTM D1238  |
| Density, (23 °C)                 | 0.960   | g/cm³    | 0.960   | g/cm³    | ASTM D1505  |
| Film                             |         |          |         |          |             |
| Tensile Strength at Yield        |         |          |         |          |             |
| MD                               | 3500    | psi      | 24.1    | MPa      | ASTM D882   |
| TD                               | 3920    | psi      | 27.0    | MPa      | ASTM D882   |
| Tensile Elongation at Break      |         |          |         |          |             |
| MD                               | 850     | %        | 850     | %        | ASTM D882   |
| TD                               | 570     | %        | 570     | %        | ASTM D882   |
| Secant Modulus                   |         |          |         |          |             |
| MD                               | 110000  | psi      | 760     | MPa      | ASTM D882   |
| TD                               | 130000  | psi      | 895     | MPa      | ASTM D882   |

LyondellBasell Technical Data Sheet Date: 2/27/2023

#### **Notes**

Data generated using 2.0 mil cast film.

These are typical property values not to be construed as specification limits.

# **Processing Techniques**

Specific recommendations for resin type and processing conditions can only be made when the end use, required properties and fabrication equipment are known.

### **Company Information**

For further information regarding the LyondellBasell company, please visit <a href="http://www.lyb.com/">http://www.lyb.com/</a>.

© LyondellBasell Industries Holdings, B.V. 2018

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative.

#### **Trademarks**

The Trademark referenced within the product name is owned or used by the LyondellBasell family of companies.

LyondellBasell Technical Data Sheet Date: 2/27/2023