



<b>Grade</b>	JSS-395N
<b>Product</b>	PP

### General Information

Key Features	<ul style="list-style-type: none"> <li>- High Stiffness and Heat resistance</li> <li>- Ultra High flow</li> </ul>
--------------	---

Applications	Industrial/Household goods, Home appliances, PP Compound Base Resin
--------------	--

Item	Measuring Method	Unit	Value
<b>Physical</b>			
Melt Flow Index	ASTM D1238	g/10min	110.0
Density	ASTM D1505	g/cm <sup>3</sup>	0.9
<b>Mechanical</b>			
Tensile Stress (Yield)	ASTM D638	kgf/cm <sup>2</sup>	300
Tensile Strain (Break)	ASTM D638	%	≤100
Flexural Modulus	ASTM D790	kgf/cm <sup>2</sup>	19,000
<b>Impact</b>			
Izod Impact Strength(notched) (23°C)	ASTM D256	kgf·cm/cm	6.0
Izod Impact Strength(notched) (-10°C)	ASTM D256	kgf·cm/cm	2.0
<b>Thermal</b>			
Heat Deflection Temperature(4.6kgf/cm <sup>2</sup> )	ASTM D648	°C	135

1. Physical Properties : these are not to be construed as specifications
2. ISO 9001, 14001, /TS 16949

\* The last update date : 2021/10/01